











STRIKE FIRST CORPORATION



777 TAPSCOTT RD.
SCARBOROUGH, ONTARIO, CANADA
M1X 1A2
PH: 416-299-7767 FAX: 416-299-8039
TOLL FREE: 1-888-575-1132
TOLL FREE FAX: 1-888-575-1134
www.strike-first.com
info@strike-first.com

10 LB. CARBON DIOXIDE (CO₂) PORTABLE FIRE EXTINGUISHER



-  WELL SUITED FOR CORROSIVE ENVIRONMENTS
-  INDUSTRIAL STRENGTH ALUMINUM CYLINDER IS UP TO 30% LIGHTER THAN STEEL
-  CHROME PLATED BRASS VALVE WITH STAINLESS STEEL HANDLES
-  STAINLESS STEEL HOSE BAND
-  STRONG IMPACT RESISTANT HORN WITH INSULATED RUBBER HANDLE
-  BAR CODED LABEL
-  EASY TO SERVICE HORIZONTAL VALVE STEM
-  COMPLETE WITH WALL HOOK
**OPTIONAL VEHICLE / MARINE BRACKET
PART No. HDVB-3 (Sold seperately)*

SPECIFICATIONS

APPROVAL		
MODEL	SF-10CO2A	WBSF-10CO2
CAPACITY	10 lbs.	
UL / ULC RATING	10-B : C	
*U.S.C.G. APPROVAL	Type B:C Size II	
RANGE	6 - 12 ft (2 - 2.5 m)	
TEMP. RANGE	-30°C to 49°C (-22°F to 120°F)	
DISCHARGE TIME	10 sec.	
HEIGHT	19 3/4" (50.2 cm)	
WIDTH	11 3/4" (30 cm)	
DIAMETER	7" (17.8 cm)	
WEIGHT	28 lbs. (12.7 kgs.)	

MANUFACTURED AND TESTED TO THE FOLLOWING STANDARDS:

ANSI/UL 154 ANSI/UL 711
CAN/ULC-S508-M90 CAN/ULC-S503-M90

CLASS: B C



6 YEAR WARRANTY