











**STRIKE FIRST  
CORPORATION**



777 TAPSCOTT RD.  
SCARBOROUGH, ONTARIO, CANADA  
M1X 1A2  
PH: 416-299-7767 FAX: 416-299-8039  
TOLL FREE: 1-888-575-1132  
TOLL FREE FAX: 1-888-575-1134  
www.strike-first.com  
info@strike-first.com

## 15 LB. CARBON DIOXIDE (CO<sub>2</sub>) PORTABLE FIRE EXTINGUISHER



-  WELL SUITED FOR CORROSIVE ENVIRONMENTS
-  INDUSTRIAL STRENGTH ALUMINUM CYLINDER IS UP TO 30% LIGHTER THAN STEEL
-  CHROME PLATED BRASS VALVE WITH STAINLESS STEEL HANDLES
-  STAINLESS STEEL HOSE BAND
-  STRONG IMPACT RESISTANT HORN WITH INSULATED RUBBER HANDLE
-  BAR CODED LABEL
-  EASY TO SERVICE HORIZONTAL VALVE STEM
-  COMPLETE WITH WALL HOOK  
*\*OPTIONAL VEHICLE / MARINE BRACKET  
PART No. HDVB-3 (Sold seperately)*

### SPECIFICATIONS

APPROVAL		
MODEL	SF-15CO2A	WBSF-15CO2
CAPACITY	15 lbs.	
UL / ULC RATING	10-B : C	
*U.S.C.G. APPROVAL	Type B:C Size II	
RANGE	6 - 12 ft (2 - 2.5 m)	
TEMP. RANGE	-30°C to 49°C (-22°F to 120°F)	
DISCHARGE TIME	15 sec.	
HEIGHT	26 1/4" (66.7 cm)	
WIDTH	11 3/4" (30 cm)	
DIAMETER	7" (17.8 cm)	
WEIGHT	37 lbs. (12.3 kgs.)	

MANUFACTURED AND TESTED TO THE  
FOLLOWING STANDARDS:

ANSI/UL 154      ANSI/UL 711  
CAN/ULC-S508-M90      CAN/ULC-S503-M90

**CLASS: B C**



**6 YEAR WARRANTY**