










# STRIKE FIRST CORPORATION



777 TAPSCOTT RD.  
SCARBOROUGH, ONTARIO, CANADA  
M1X 1A2  
PH: 416-299-7767 FAX: 416-299-8039  
TOLL FREE: 1-888-575-1132  
TOLL FREE FAX: 1-888-575-1134  
www.strike-first.com  
info@strike-first.com

## 5 LB. CARBON DIOXIDE (CO<sub>2</sub>) PORTABLE FIRE EXTINGUISHER



-  WELL SUITED FOR CORROSIVE ENVIRONMENTS
-  INDUSTRIAL STRENGTH ALUMINUM CYLINDER IS UP TO 30% LIGHTER THAN STEEL
-  CHROME PLATED BRASS VALVE WITH STAINLESS STEEL HANDLES
-  STRONG IMPACT RESISTANT HORN
-  BAR CODED LABEL
-  EASY TO SERVICE HORIZONTAL VALVE STEM
-  COMPLETE WITH WALL HOOK  
*\*OPTIONAL VEHICLE / MARINE BRACKET  
PART No. HDVB-2 (Sold seperately)*

### SPECIFICATIONS

| APPROVAL           |  |  |
|--------------------|---|---|
| MODEL              | SF-5CO2A  | WBSF-5CO2   |
| CAPACITY           | 5 lbs.  |   |
| UL / ULC RATING    | 5-B : C   |   |
| *U.S.C.G. APPROVAL | Type B:C Size I   |   |
| RANGE              | 6 - 12 ft (2 - 2.5 m)   |   |
| TEMP. RANGE        | -30°C to 49°C (-22°F to 120°F)  |   |
| DISCHARGE TIME     | 10 sec.   |   |
| HEIGHT             | 17 1/4" (44 cm)   |   |
| WIDTH              | 8 1/2" (21.6 cm)  |   |
| DIAMETER           | 5 1/4" (13.3 cm)  |   |
| WEIGHT             | 13 1/2 lbs. (6.12 kgs.)   |   |

MANUFACTURED AND TESTED TO THE FOLLOWING STANDARDS:

ANSI/UL 154                      ANSI/UL 711  
CAN/ULC-S508-M90          CAN/ULC-S503-M90

**CLASS: B C**



**6 YEAR WARRANTY**